

ConSpare

Make it better.

DataSheet

DuraFlex Sleeve

DuraFlex connectors are the bespoke option within our sleeving range. The connectors are constructed from a flexible natural rubber, which is then formed using a reinforced cold bonded joint. This process allows us to offer connectors in a vast range of diameters and lengths to suit client requirements on a quick turnaround. The flexibility of the rubber makes DuraFlex connectors particularly useful where weighing equipment is being connected.

DuraFlex is available in 3mm, 6mm, 8mm and 10mm thicknesses. The wear resistant rubber is 40 shore (A) hardness, and has a maximum short-term operating temperature of 80°C.



Custom jointed connectors

Highly flexible rubber

Short lead times

40 shore (A) hardness

Maximum short-term temperature 80° C

3mm, 6mm, 8mm and 10mm thicknesses

As DuraFlex connectors are made to order. Please provide the following information to obtain a quotation.

CONTACT DETAILS	
Company:	Site address:
Name:	
Email:	
SLEEVE REQUIREMENTS	
Material handled:	Quantity required:
Length: mm	Inside Diameter (ID): mm
Wall thickness:	3mm 6mm 8mm 10mm

Visit - www.conspare.com | Call +44 (0)1773 860796 | Email - sales@conspare.com

ConSpare Limited Registered in England No. 10373473
Castlewood Business Park, Farmwell Lane, Sutton-in-Ashfield, Nottinghamshire. NG17 1BX.
We reserve the right to modify or withdraw specifications or products without notice or obligation.

